

DSX SEED DRILL

HORIZON
AGRICULTURE

OVERVIEW

At Horizon, we believe that it is vitally important for the future of our industry, that as farmers, we properly preserve, maintain and replenish our soil. This philosophy is at the heart of everything that we do.

The Horizon DSX is the ultimate direct seed drill. Designed and developed using lessons learned from generations of hands-on experience and featuring cutting-edge technology, resulting in a machine that effectively delivers accurate, consistent seed placement and with minimal soil disturbance on every pass.

We are truly committed to manufacturing innovative products that promote soil regeneration, whilst also helping our customers to improve productivity, yield and profitability.

BENEFITS

- Designed, developed and manufactured in Great Britain
- Unique modular and upgradeable design
- Adapts and grows with your business
- Reliable and durable
- Minimal soil disturbance
- Split seeding options
- Optional Precision Planting technology



DIMENSIONS

Frame	4m				4.8m				6m				6.4m			
Rows	24	22	20	16	28	26	24	19	36	32	30	24	38	34	32	26
Spacing (cm)	16.7	18.75	20	25	16.7	18.75	20	25	16.7	18.75	20	25	16.7	18.75	20	25
Transport width (folded) (m)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Transport height (folded) (m)	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7
Transport length (folded) (m)	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5

Frame	7.2m				7.5m				8m				9m			
Rows	43	38	36	29	45	40	38	30	48	43	40	32	54	48	45	36
Spacing (cm)	16.7	18.75	20	25	16.7	18.75	20	25	16.7	18.75	20	25	16.7	18.75	20	25
Transport width (folded) (m)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.4	3.4	3.4	3.4
Transport height (folded) (m)	4.1	4.1	4.1	4.1	4.25	4.25	4.25	4.25	3.7	3.7	3.7	3.7	3.95	3.95	3.95	3.95
Transport length (folded) (m)	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5

Hopper capacity (l) (60:40 hopper)	2640:1760
Hopper capacity (l) (60:10:30 hopper)	2640:440:1320
Fan	Hydraulic
Hitch type	CAT III

PRECISION PLANTING TECHNOLOGY

-	-
-	-
-	-
-	-
-	-

-	-
-	-
-	-
-	-
-	-

FEATURES

RDS ISOCAN	Standard
Hydraulic brakes	Standard
Front / rear hopper separation	Standard
710 / 50 wheels	Standard
"V" press wheel	Standard
Variable seed rate	Optional
GPS variable seed rate	Optional
Internal disc scraper	Optional
Variable rate unlock	Optional
Tramline valves 2 or 4	Optional
Hopper / reversing cameras	Optional
Blockage sensors	Optional
Front trash wheels with CleanSweep control	Optional
Rear trash wheels with CleanSweep control	Optional
"W" press wheel	Optional
850 wheels and tyre upgrade	Optional
Air brakes	Optional
Seed firmers	Optional
ISOBUS cable (power from ISOBUS socket)	Optional
Liquid fertiliser kit (1500L tank and 30 l/min) pump and controller	Optional